



THE SYNTHETIC TURF SPECIALISTS
MANUFACTURING SPORTS,
LANDSCAPE & LEISURE SURFACES



Technical Specifications

Product code:

Summit 4515

Suitable usage:

Landscape

Configuration

Machine gauge:

9.52mm (3/8")

Pile height:

45mm (+/- 3%)

Stitch rate:

17 per 100mm (+/- 3%)

Yarn weight:

1460 grams per sq metre

Yarn properties

Construction:

Twisted KDK fibrillated tape, polyethylene monofilament

Linear density:

1050 tex (+/- 3%)

Colour:

Two tone

U.V Stability:

Yarn is protected against Ultraviolet degradation to the highest level as specified in the yarn manufacturers warranty terms and conditions

Primary backing

No. of layers:

Double

Construction:

Woven polypropylene

Colour:

Black

Secondary coatings

Compound base:

Carboxylated self curing styrene butadiene rubber latex

Tuft anchorage:

27 newtons (minimum)

Colour:

Black

Antioxidizing agent:

Present

Product warranty

Finish product:

10 year limited warranty as per manufacturers standard warranty terms

SYNTURF PTY LTD

18 Kurnai Ave, Reservoir 3073 ph: +61 3 9460 2209 fax: +61 3 9460 2219 email: sales@synturf.com.au

Thinking Synthetic Turf... Think Synturf

www.synturf.com.au